



Raytheon

Santa Barbara
Remote Sensing

MODIS Science Team Meeting FM1 Status

**NASA GSFC
Contract No. NAS 5-30800**

15 December 1998

Raytheon



Agenda

Raytheon

Santa Barbara
Remote Sensing

- **Overview**
- **TV Performance**
 - **Crosstalk Performance**
 - **Spectral Performance**
 - **Radiometric**
 - **OBC Calibrators**
- **Ambient FM1 RVS Update**
- **Issues**
- **Summary**




FM1 Thermal Vacuum Test Has Been Completed

Raytheon

Santa Barbara
Remote Sensing

FM1 MODIS Instrument Thermal-Vacuum/Thermal Cycle Timeline






FM1 SWIR Crosstalk Significantly Better than PFM

Raytheon

Santa Barbara
Remote Sensing

Crosstalk From Band 6 Sender at Optimum Itwk/Vdet vs PFM






FM1 MWIR Crosstalk Significantly Better than PFM

Raytheon

Santa Barbara
Remote Sensing

Crosstalk From Band 20 Sender at Optimum Itwk/Vdet vs PFM






FM1 LWIR Crosstalk Significantly Better than PFM

Raytheon

Santa Barbara
Remote Sensing

Crosstalk From Band 29 at Optimum Itwk/Vdet vs PFM





Radiometric Performance

Raytheon

Santa Barbara
Remote Sensing


- Preliminary results show excellent instrument performance
- Many, Many RC01/RC02 data sets acquired AND analyzed
- SNRs/NE Δ Ts/Linearity has been characterized, save for radiometric coefficients
- CPA/PRI and CPA/RDT form calibration data set
 - Covers BOTH sides of all FPA analog signal trains
- Redundant side not calibrated with CPB
 - Issues remain on CPB/RDT “drift” anomaly



Primary SNRs Compliant For Reflective Bands

Raytheon

Santa Barbara
Remote Sensing




- Two failed channels for Band 6 (7 and 19) documented
- EFR1732 (Waiver required)



Primary NEdT's Compliant For Emmissive Bands

Raytheon

Santa Barbara
Remote Sensing



- Low signal on Band 21 believed to be cause of non-compliances
- EFR1733 (Waiver required)



Spectral Performance

Raytheon

Santa Barbara
Remote Sensing

- **In-band data is spec compliant for most bands**
- **All Data Processed**
 - **In-Band Ambient (VIS,NIR) and TV Nominal (SW,MW,LW)**
 - **TV NLT**
 - > Shifts consistent with published literature
 - **Special Collects**
 - > Bands 20 and 31 vs Instrument temperature
 - > Band 27 for SPMA Purge Characterization
 - > Band 35 acquired at 2nm intervals for CO2 characterization




Center Wavelength Requirements Achieved by Most Bands

Raytheon

Santa Barbara
Remote Sensing

Measured vs Spec Center Wavelength Tolerance as a Percentage of Center Wavelength Requirement






Bandwidth Requirements Achieved by Most Bands

Raytheon

Santa Barbara
Remote Sensing

Measured vs Spec Bandwidth Tolerance as a Percentage of Bandwidth Requirement





Out-of-Band Data Analysis in Process

Raytheon

Santa Barbara
Remote Sensing

- All OOB data has been quiklooked
- Detailed DN level reductions completed
 - Normalizations in process
 - Limited OOB results generated
 - > 5.3 μm leak on PFM is reduced on FM1, but NOT eliminated (based on BCS results)
 - Band 5 -> Approximately 3x reduction
 - Band 6 -> Approximately 4x reduction
 - Band 26 -> Approximately 2x reduction
 - > 11 μm leak on FM1 << PFM
 - ~0.2%




PFM Band 35

Raytheon

Santa Barbara
Remote Sensing

Band 35 Out of Band Dispersive Response






FM1 Band 35

Raytheon

Santa Barbara
Remote Sensing

FM1 Band 35 Out of Band Dispersive Response






FM1 SRCA Registration Scan Direction (Nominal)

Raytheon

Santa Barbara
Remote Sensing






FM1 SRCA Registration Track Direction (Nominal)

Raytheon

Santa Barbara
Remote Sensing






OBC BB EMITTANCE EVALUATION NOMINAL PLATEAU




Santa Barbara Remote Sensing

- BCS constant temperature @ $\approx 285K$
- MFI09 transition $\approx 285K$ used for OBC BB data set
- Signal levels and emittance are illustrated



$$T2_{bcs} = 285.137 \quad \text{mean}(\epsilon_{avg}) = 0.9993$$

$$T2_{obc} = 284.945 \quad \text{std}(\epsilon_{avg}) = 0.001$$





Response vs Scan Angle (PC20) VIS/NIR/SWIR Assessment

Raytheon

Santa Barbara
Remote Sensing

- **VIS / NIR / SWIR meets 0.5 % requirement**
 - **VIS / NIR response vs scan angle results good to ≈ 0.2 %**
 - **SWIR response vs scan angle results good to ≈ 0.4 %**
 - **Channel to channel uniformity better than 0.1 %**
 - **Residual to second order polynomial fit is less than 0.15 % except band 26 less than 0.3 %.**
 - **Residual for the third order polynomial are the same.**
- **FOV: No vignetting of NIR indicates field of view spec met**



MWIR / LWIR RVS much better than PFM

Raytheon

Santa Barbara
Remote Sensing

- **MWIR / LWIR does not meet internal 0.1 % requirement; however ...**
 - **PL3095-N06822 alternatives - witness mirror (NPL) and on orbit measurements**
 - **Bands 20 to 28 - 0.12 to 0.18 %; bands 29 & 30 - 0.3 to 0.4 %; bands 31 to 36 - 0.12 % to 0.25 %**
- **Data reduction/analysis is continuing**
 - **Acquired data includes: BCS, SVS, and OBC BB sources**
 - **Channel to channel data (unsaturated) is clustered**
 - **Data is much better than that acquired on PFM**
 - **Reduction of all data sets not completed**
 - **Data sets with BCS 320 K side A and B; BCS 310 K side A done**
 - **Uncertainty assessment continues**



COMPARISON OF HIGH BAY RVS TO NPL REFLECTANCE II

- Ratio of high bay RVS to NPL reflectance, R1
- Average and standard deviation of R1 given in array "stat"


R1 =	0	10	26.5	38	50	60.5	65.5	■	stat	20	1.0038	0.001	■
	20	1	1.005	1.005	1.005	1.003	1.002			22	1.0027	0.0009	
	22	1	1.004	1.003	1.002	1.003	1.001			23	1.0026	0.0002	
	23	1	1.003	1.002	1.001	1.005	1.002			24	1.0033	0.0001	
	24	1	1.003	1.003	1.004	1.003	1.003			25	1.0027	0.0006	
	25	1	1.002	1.002	1.003	1.003	1.004			27	1.0026	0.0021	
	27	1	1	1	1.001	1.005	1.007			28	1.0035	0.0005	
	28	1	1.005	1.004	1.003	1.004	1.003			29	0.994	0.006	
	29	1	1.007	1.001	0.993	0.987	0.982			30	0.9976	0.0002	
	30	1	1	0.997	0.995	0.998	0.998			31	0.9988	0.0021	
	31	1	1.004	1.002	0.998	0.996	0.995			32	0.9999	0.0009	
	32	1	1.003	1.002	0.998	0.998	0.998			33	1.0041	0.0002	
	33	1	1.007	1.004	1.002	1.004	1.004			34	1.0061	0.0009	
	34	1	1.007	1.006	1.004	1.005	1.008			35	1.0059	0.0007	
	35	1	1.008	1.007	1.003	1.004	1.007			36	1.0078	0.0018	
	36	1	1.009	1.008	1.004	1.006	1.011						



COMPARISON OF HIGH BAY RVS TO NPL REFLECTANCE IV

Raytheon

Santa Barbara
Remote Sensing



- Middle curve is average ratio of high bay RVS to NPL reflectance.
- Vertical bars represent $\pm 1 \sigma$ obtained from high bay to NPL comparison
- Envelope curves obtained by combining NPL and high bay estimated uncertainty in quadrature.



Issues

Raytheon

Santa Barbara
Remote Sensing

- **Power supply resets**
- **PC detector response drift anomaly**
 - > Telemetry/science data vs LW/SM HTR, PRI/RDT crosstrap modes to the TCPs, FPA temperature, timing, and FPAs on/off
 - > Occurs with CPB, LW Heater, NIR FPA on, and sector timing re-synchs enabled
 - > Ambient diagnostics in process; Drift has been observed in ambient
- **NAD/SDD fail-safe operation**
 - > NAD counterweights installed improperly
 - > Blanket ground wire interference discovered on SDD



Summary

Raytheon

Santa Barbara
Remote Sensing

- **TV test yielded impressive instrument performance**
 - Significantly reduced crosstalk observed compared to the PFM
 - SNR/NE Δ T, spectral, spatial predominantly in spec
 - Post-TV tests going well wrt door, PS, and PC “drift” anomalies
- **Extremely well coordinated effort; Thanks to all who participated, including NASA/MCST**
- **Key tasks remaining**
 - Finish ambient analyses (RVS, Stray Light)
 - Prepare for PSR
 - > Specifically spectral reductions, waivers, final paper



VIS/NIR/SWIR Spectral Parameters Summarized

Raytheon

Santa Barbara
Remote Sensing

Band	Channel	CW50%Meas	CWCentMeas	CWSPEC	BWMEAS	BWSPEC	ER1MEAS	ER2MEAS	ERSPEC	RippleMEAS	RippleSPEC
8	5	412.0	412.3	412.0	14.4	15.0	12.8	4.1	7.2	80.5%	80.0%
9	5	442.1	442.1	443.0	9.7	10.0	4.9	3.8	4.9	93.4%	80.0%
3	10	465.9	465.8	469.0	18.9	20.0	4.7	6.0	9.5	81.2%	80.0%
10	5	487.3	487.2	488.0	10.7	10.0	4.0	3.1	5.4	80.9%	80.0%
11	5	530.1	530.0	531.0	12.0	10.0	4.4	5.0	6.0	80.0%	80.0%
12	5	547.1	547.0	551.0	10.4	10.0	5.1	4.8	5.2	85.3%	80.0%
4	10	553.8	553.8	555.0	19.8	20.0	5.4	5.3	9.9	84.7%	80.0%
1	20	644.8	645.8	645.0	47.5	50.0	20.8	13.8	23.8	80.7%	80.0%
13	5	665.8	665.8	667.0	10.1	10.0	4.8	5.7	5.1	84.1%	80.0%
14	5	677.4	677.3	678.0	11.4	10.0	5.8	5.4	5.7	87.6%	80.0%
15	5	746.6	746.5	748.0	9.8	10.0	5.5	5.4	4.9	86.8%	80.0%
2	20	857.0	856.5	858.0	38.1	35.0	16.5	13.2	19.1	90.4%	80.0%
16	5	866.8	866.6	869.0	15.5	15.0	7.5	6.9	7.8	86.2%	80.0%
17	5	904.2	904.2	905.0	35.0	30.0	13.0	12.6	17.5	90.8%	80.0%
18	5	936.1	936.1	936.0	13.6	10.0	7.1	6.5	6.8	84.6%	80.0%
19	5	935.4	936.0	940.0	46.7	50.0	20.9	19.1	23.4	80.5%	80.0%
5	10	1241.4	1241.3	1240.0	23.0	20.0	14.5	13.5	11.5	80.1%	80.0%
26	6	1383.2	1381.8	1375.0	36.5	30.0	28.6	18.8	18.3	83.5%	80.0%
6	10	1627.7	1627.6	1640.0	27.7	24.6	15.7	16.2	13.9	85.8%	80.0%
7	10	2113.0	2113.5	2130.0	53.1	50.0	21.9	42.4	26.6	80.9%	80.0%

- Parameters in nm units



MW/LW Spectral Parameters Summarized

Raytheon

Santa Barbara
Remote Sensing

Band	Channel	CW50%Meas	CWCentMeas	CWSPEC	BWMEAS	BWSPEC	ER1MEAS	ER2MEAS	ERSPEC	RippleMEAS	RippleSPEC
20	5	3776.7	3778.4	3750.0	189.6	180.0	51.0	54.5	94.8	78.7%	80.0%
21	5	3980.4	3980.2	3959.0	84.4	59.4	39.4	40.1	42.2	86.8%	80.0%
22	5	3971.0	3970.5	3959.0	85.9	59.4	38.7	30.3	43.0	82.3%	80.0%
23	5	4059.7	4059.6	4050.0	86.3	60.8	35.9	32.0	43.2	85.2%	80.0%
24	5	4447.9	4447.3	4465.0	92.2	65.0	44.2	38.3	46.1	81.1%	80.0%
25	5	4524.5	4524.5	4515.0	91.6	67.0	47.4	37.2	45.8	83.4%	80.0%
27	5	6780.7	6782.1	6715.0	192.5	360.0	181.2	169.6	96.3	80.1%	80.0%
28	5	7339.6	7341.2	7325.0	321.1	300.0	146.4	162.9	160.6	82.7%	80.0%
29	5	8547.8	8545.3	8550.0	376.3	300.0	198.4	140.9	188.2	81.6%	80.0%
30	5	9726.3	9716.2	9730.0	317.9	300.0	178.1	200.7	159.0	80.5%	80.0%
31	5	11026.8	11024.8	11030.0	530.8	500.0	269.4	267.4	265.4	80.8%	80.0%
32	5	12043.5	12039.9	12020.0	522.1	500.0	117.3	139.1	261.1	82.0%	80.0%
33	5	13362.4	13361.2	13335.0	313.9	300.0	110.8	121.6	157.0	86.9%	80.0%
34	5	13679.6	13680.9	13635.0	345.7	300.0	122.6	119.5	172.9	84.5%	80.0%
35	5	13920.5	13920.1	13935.0	335.0	300.0	114.5	117.8	167.5	81.3%	80.0%
36	5	14215.3	14209.6	14235.0	330.4	300.0	128.4	133.8	165.2	81.2%	80.0%

- Parameters in nm units




VIS Bands

Raytheon

Santa Barbara
Remote Sensing

**FM1 VIS Spectral Response
Bands 8, 9, 3, 10, 11, 12, 4**






NIR Bands

Raytheon

Santa Barbara
Remote Sensing

FM1 NIR Spectral Response
Bands 1, 13, 14, 15, 2, 16, 17, 18, 19






SWIR Bands

Raytheon

Santa Barbara
Remote Sensing

**FM1 SWIR Spectral Response
Bands 5, 26, 6,7**






MWIR Bands

Raytheon

Santa Barbara
Remote Sensing

**FM1 MWIR Spectral Response
Bands 20, 22, 21, 23, 24, 25**






PV LWIR Bands

Raytheon

Santa Barbara
Remote Sensing

**FM1 PVLW Spectral Response
Bands 27, 28, 29, 30**






PC LWIR Bands

Raytheon

Santa Barbara
Remote Sensing

**FM1 PCLWIR Spectral Response
Bands 31, 32, 33, 34, 35, 36**





Tabulated RVS (MWIR / LWIR)



Santa Barbara
Remote Sensing

- Tabulated normalized RVS based upon BCS 320 K, side A
- Scan angle and AOI given in degrees - row 1 & 2

320	-54.5	-54	-53	-45	-23	0	10	26	38	45	50	53	54	54.5
band	10.75	11	11.5	15.5	26.5	38	43	51	57	60.5	63	64.5	65	65.25
20	1	0.997	1.000	0.997	1.001	1.002	0.997	0.998	1.000	0.996	0.995	0.997	0.999	0.995
22	1	1.001	0.999	0.999	1.000	1.001	0.997	1.000	0.999	0.999	0.996	0.994	1.000	0.993
23	1	0.997	0.998	0.998	0.998	1.000	0.995	0.998	0.998	0.995	0.998	0.998	0.998	0.997
24	1	0.997	1.000	0.996	1.000	1.001	0.997	0.997	1.001	0.998	0.997	0.999	1.000	0.997
25	1	0.997	0.998	0.997	0.997	1.000	0.995	0.997	0.999	0.997	0.999	0.999	0.998	0.997
27	1	1.002	1.002	1.000	0.998	0.997	0.995	0.999	0.998	0.998	0.997	1.000	0.996	0.999
28	1	0.997	0.996	0.996	0.996	0.999	0.993	0.994	0.994	0.988	0.991	0.990	0.991	0.987
29	1	0.995	0.991	0.988	0.986	0.979	0.973	0.964	0.942	0.934	0.926	0.925	0.922	0.922
30	1	0.989	0.983	0.985	0.981	0.977	0.968	0.968	0.952	0.955	0.948	0.946	0.947	0.944
31	1	1.001	0.999	0.999	0.998	0.994	0.988	0.984	0.978	0.974	0.970	0.966	0.971	0.965
32	1	1.001	1.000	0.999	0.997	0.993	0.986	0.979	0.971	0.966	0.962	0.958	0.962	0.955
33	1	1.000	1.000	0.998	0.993	0.985	0.976	0.961	0.948	0.938	0.933	0.926	0.928	0.919
34	1	1.000	1.001	0.999	0.993	0.985	0.975	0.959	0.944	0.935	0.930	0.924	0.926	0.915
35	1	1.000	1.001	0.999	0.992	0.985	0.974	0.956	0.941	0.931	0.927	0.920	0.922	0.911
36	1	1.001	1.002	0.999	0.992	0.984	0.974	0.954	0.939	0.929	0.926	0.918	0.919	0.908